

K

Test Equipment



Micro Hardness Testing Machines



Rockwell Hardness Testing Machines



Micro Zone Test System



Portable Hardness Testing Instruments



HARDMATIC HH-411



AAV-500

INDEX

Test Equipment

Micro Hardness Testing Machines

Lineup of Hardness Testing Machines	K-2,3
HM-101 / 112 / 113 / 122	K-4
HM-210 / 220	K-5
AAV-500	K-6
MZT-500	K-7
HV-112 / 113 / 114 / 115	K-8
Optional Accessories Micro-Vickers/Vickers Hardness Testing Machine	K-9,10

Rockwell Hardness Testing Machines

HR-521(L) / 523(L)	K-11
HR-210MR/320MS/430MR/430MS	K-12
Optional Accessories For Rockwell/Rockwell Superficial Type Hardness Testing machine	K-13,14

Portable Hardness Testing Machines

Hardmatic HH-411	K-15
Hardmatic HH-300	K-16
Hardmatic HH-300 Test Block Set	K-17



HR-210MR



HR-320MS



HR-430MR




HR-430MS


Lineup of Hardness Testing Machines

Hardness testing machines provide the simplest and most economical testing methods among many material testing machines, playing an important role in research activities, production activities, and commercial transactions. Mitutoyo offers a choice of standard hardness testing machines that are optimal for hard materials such as metals to soft materials such as plastic and rubber, as well as custom-designed testers such as in-line type automatic machines and labor-saving machines required on the shop floor.






Polished Surface



Scratched Surface




Ground Surface

Vickers Hardness

In the Vickers hardness test, a diamond pyramid indenter with a 136° angle between opposite faces is pressed into the specimen under a test force F (kgf). The hardness number (HV) is obtained by dividing F by the area, A (mm^2), of contact between the indenter and specimen. This area is calculated from the diagonal length, d (mm), of the indentation when the indenter is removed.

The Vickers hardness test is the most versatile hardness testing method of those that use different load settings. The Micro-Vickers hardness test, which accepts load settings of 1 kgf (9.807N) or less, is especially well suited for industrial production today, where accuracy requirements are increasing due to technology improvements.


Vickers hardness testing at loads of 1 kilogram and up is also known as heavy load Vickers or Macro Vickers. The other testing parameters are similar to lighter load vickers testing. This type of testing may be used to meet the requirements of international specifications or to replace Rockwell testing.



Knoop Hardness

In the Knoop hardness test, a diamond pyramid indenter, which has a rhombic base with included angles of $172^\circ 30'$ and 130° , is pressed onto the specimen under a test force F (kgf). The hardness number (HK) is obtained by dividing the test force F by the projected area, A (mm^2), of the indentation. This area is calculated from the longer diagonal length, d (mm), of the indentation when the indenter is removed.

The Knoop hardness scale is generally used when shallower depth indentations are required. Knoop hardness can be measured by installing a Knoop indenter on the Macro-Vickers hardness testing machine.



HM-101 / 112 / 113 / 122

SERIES 810 — Micro-Vickers Hardness Testing Machines

FEATURES

- A wide range of test force from 9.807 X10-3N to 9.807N (10gf to 1000gf) is available for measuring a various type of specimens. The load duration can be set in 1sec increments between 5 and 99 sec*. The minimum reading of indentation is 0.01µm* and allows small indentations to be measured with high precision. *HM-112, HM-113
- Up to 3 Objective lenses and 1 or 2 indenters mounted on manual or motorized turret
- Eyepiece or CCTV
- Measuring Versions
- Camera port



HM-113 Reduce individual differences in visual measurement with the TV monitor. The statistical calculation function reduces operation time.

HM-112 Digital display of measurement results and a statistical calculation function.



Touch screen type




HM-101

SPECIFICATIONS

Model	HM101	HM-112	HM-113	HM122 V	HM122 V/K
Order No.	810-124A	810-126-07A	810-969A	810-127-01A	810-127-02A
Supplied Indenter	VICKERS				VICKERS/KNOOP
Test force*	98.07mN(10g), 245.2mN(25g), 490.3mN(50g), 980.7mN(100g), 1961mN(200g), 2942mN(300g), 4903mN(500g), 9807mN(1000g)				
Test force selection	Dial				
Loading control	Automatic (loading, duration, unloading)				
Load duration	5s-30s	5s to 99s (specified in 1-second increments)			
Loading Rate	60µm/sec.				
Objective Lenses	10x, 50x	10x, 50x		10x, 20x, 50x	
Turret	Manual			Motor Drive	
Measuring microscope total magnification	100x, 500x	100x, 500x		100x, 200x, 500x	
Video monitor screen	—	—	9" B/W 250x, 1250x	—	—
Total Magnification	—	—	—	—	—
Filar eyepiece	10x	10x	—	10x	10x
Minimum reading	0.2mm	0.01µm			
Maximum Reading	140µm	700 / 140µm	500 / 100µm	700 / 350 / 140µm	
Type	Micrometer Drum	Digital Optical Encoder			
XY stage					
Dimension	4 x 4" (100 x 100mm)				
Travel range	1 x 1" (25 x 25mm)				
Minimum reading	.005" (0.01mm)	.0005" (0.001mm)			
Specimen					
Maximum height	3.75" (95mm)				
Maximum depth	5.91" (150mm)				
Display Function	Conversion; Hard: TENS, HS, HBS, HR15N, HR30N, HR45N, HRA, HRD, HRC, HK, HV, OFF Soft: TENS, HR15T, HR30T, HR45T, HRA, HRF, HRB, HRG, HK, HV, OFF OK/NG Judgement Curve correction: 0.01 to 200.00mm Data processing; Number to measurements 2 to 256 data Statistical list: N, Max., Min., Average, Range, High, Low, Good, Over, Under, SD(n-1), SD(n)				
Output	RS-232C, SPC, Centronics				
Dimensions	Main unit: W=16.1 x D=23.6 x H=23.2" (410 x 600 x 590mm) Display: W=6.5 x D=10.2 x H=4.1" (165 x 260 x 105mm)				
Weight	Main unit: 92.4 lbs. (42kg)				
Power supply	120V AC (±10%), 60 Hz				
Power consumption	20VA	60VA			

Optional Accessories

See Page K-9



Technical Data

Test force range:
 HM-210A: 9 steps + arbitrary test force
 HM-220A: 19 steps + arbitrary test force
 Load dwell time: 0 - 999s
 Manual XY stage unit
 Stage size: 100x100mm
 Travel range: 25x25mm
 with Digimatic in/mm micrometer heads
 Resolution: 0.001mm
 Max. specimen height: 133mm (Stage size: 25 x 25mm)
 Max. specimen height: 121mm (Stage size: 50 x 50mm)
 Max. specimen depth: 160mm (from the center of indenter)
 Optical path: 4-port objectives switching system of
 Infinity-correction optical system
 Resolution: 0.01µm (When using objectives of X40 or more)
 Data output: Serial interface (RS-232),
 Digimatic interface, USB 2.0
 Power supply: 39VA 100-125/220-240V AC, 50/60Hz
 Dimensions: (W x D x H): 315x671x595mm
 Mass: 43kg

Optional Accessories (Factory-installed option)

11AAC104: Objective lens unit 2X
11AAC105: Objective lens unit 5X
11AAC106: Objective lens unit 10X
11AAC107: Objective lens unit 20X
11AAC108: Objective lens unit 100X
11AAC129: Measuring microscope (Digital ocular)
11AAC109: Knoop Indenter Assembly (HM-210 Series)
11AAC110: Knoop Indenter Assembly (HM-220 Series)


Optional Accessories

810-354A: TV camera unit (8.4 inch LCD)
19BAA058: Diamond indenter for Vickers (HM210 Series standard test force)
19BAA059: Diamond indenter for Vickers (HM220 Series low test force)
19BAA061: Diamond indenter for Knoop (HM210 Series)
19BAA062: Diamond indenter for Knoop (HM220 Series)
810-017: Vise
810-013: Specimen (thin plate) holder
810-014: Specimen (wire) holder
810-015: Specimen (wire or ball) holder
810-019: Specimen tilting holder
810-020: Universal specimen holder
810-018: Rotary table
810-084: Rotatable universal specimen holder
810-085: Adjustable specimen (thin plate) holder
810-095: Rotatable specimen stage
375-056: Stage Micrometer (glass) Micro-scale
810-650-1: Resin mold specimen stage ø25.4
810-650-2: Resin mold specimen stage ø30
810-650-3: Resin mold specimen stage ø31.75
810-650-4: Resin mold specimen stage ø38.1
810-650-5: Resin mold specimen stage ø40
02ATE760: Table
810-641: Vibration Isolator
810-870A: Sample Heating Device HST-250
810-420: 25x25mm stage (metric only)
810-423: 50x50mm stage (metric only)
810-424: 1"x1" in/mm stage (standard)
810-427: 2"x2" in/mm stage



Power turret with up to 2 indenter mounts and 4 objective mounts (manual operation possible)

Touch-screen type control panel



HM-210 / 220

SERIES 810 — Micro Vickers Hardness Testing Machines

FEATURES

- The latest technology electromagnetic force motor used in the loading mechanism enables the test force to be freely selected (see test force specifications) over the wide range of 0.4903mN to 19610mN (0.05gf to 2 kgf). It is also possible to freely set load dwell times. Now your desire for absolute control over the indentation size in Vickers hardness testing can be satisfied. The HM-200 series always offers the test force most appropriate for the specimen material and shape.
- The long working distance objectives used enable a very comfortable working distance between the objective and the specimen surface. This, greatly reduces the possibility of collision between the specimen and the objective during focusing operations. (e.g. for 50X objectives: 1.1mm for conventional models, 2.5mm for HM-200 series)
- Newly-designed 'MH Plan' objectives are optimized for measuring indentation images. The lineup includes 6 types of long working distance objectives: 10X, 20X, 50X and 100X for measuring indentation images, and 2X and 5X for enabling wide-range measurement around indentations.
- LEDs, which have a longer life, produce less heat, consume less power and are more energy efficient than incandescent bulbs, are employed for the illumination system.
- The motorized turret allows for up to 4 objective lenses and 2 indenter assemblies to be mounted at the same time.



Stray light reduction around the indentation



HM-210A

SPECIFICATIONS TYPE A Digital Hardness Tester

Model No.	HM-210 Type A	HM-210 Type A V/K	HM-220 Type A	HM-220 Type A V/K
Part No.	64AAB305	64AAB306	64AAB307	64AAB308
Fixed test force (mN)	98.07, 196.1, 294.2, 490.3, 980.7, 1961, 2942, 4903, 9807 (10gf-1000gf)		0.4903, 0.9807, 1.961, 2.942, 4.903, 9.807, 19.61, 29.42, 49.03, 98.07, 196.1, 294.2, 490.3, 980.7, 1961, 2942, 4903, 9807, 19610 (0.05 gf-2kgf)	
Arbitrary test force	≤100 gf in 1 gram increments, > 100gf in 10 gram increments		< 1 gf in .1 gf increments, ≤100 gf in 1 gram increments, > 100gf in 10 gram increments	
Test force control	Force generation by electromagnetic and automatic control (load, dwell, unload)			
Control unit	Color LCD Touch Screen			
Loading Rate	60 µ/sec		11, 33, 60 µ/sec	
Load Dwell Time	0-999 sec			
Indenter	Vickers	Vickers and Knoop	Vickers	Vickers and Knoop
Objective Lenses	10x, 50x	10x, 20x, 50x	10x, 50x, 100x	10x, 50x, 100x
Objective turret	Motor driven and manual operation			
Filar Eye Piece	Dual Line, 10X, .01µ min			

SPECIFICATIONS TYPE B PC Driven Test System

Model No.	HM-210 Type B	HM-210 Type B V/K	HM-220 Type B	HM-220 Type B V/K
Part No.	64AAB323	64AAB324	64AAB325	64AAB326
Fixed test force (mN)	98.07, 196.1, 294.2, 490.3, 980.7, 1961, 2942, 4903, 9807 (10gf-1000gf)		0.4903, 0.9807, 1.961, 2.942, 4.903, 9.807, 19.61, 29.42, 49.03, 98.07, 196.1, 294.2, 490.3, 980.7, 1961, 2942, 4903, 9807, 19610 (0.05 gf-2kgf)	
Arbitrary test force	≤100 gf in 1 gram increments, > 100gf in 10 gram increments		< 1 gf in .1 gf increments, ≤100 gf in 1 gram increments, > 100gf in 10 gram increments	
Test force control	Force generation by electromagnetic and automatic control (load, dwell, unload)			
Control unit	None, By PC*			
Loading Rate	60 µ/sec		11, 33, 60 µ/sec	
Load Dwell Time	0-999 sec			
Indenter	Vickers	Vickers and Knoop	Vickers	Vickers and Knoop
Objective Lenses	10x, 50x	10x, 20x, 50x	10x, 50x, 100x	10x, 50x, 100x
Objective turret	Motor driven and manual operation			
Filar Eye Piece	None			
CCTV Camera	3 megapixel, 1/2"		3 megapixel, 1/2"	
Software	AV Pak		AV Pak	

*Must use specified PC

AAV-500

SERIES 810 — Automatic Vickers Hardness Testing System

FEATURES


It can perform all operations required in the Vickers hardness test and Knoop hardness test such as loading, turret indexing, focusing, indentation dimension detecting, and measurement position movement in full automatic, so it is optimal for labor saving requirements of your test environment.



AAV-503/504

- An indentation dimension automatic detecting time of 0.3 seconds is achieved (when a PC with recommended specifications is used), which dramatically improves operation efficiency.
- Detecting reproducibility of $\pm 0.5\%$ is achieved (For objective lens 50X, diagonal line 11 to 45mm, and 500HV), which provides reliable and stable test results.
- All operations from test condition setting to test result analysis can be performed on a Windows PC. In addition, data processing for the test results can be performed by using spreadsheet software.

The AAV-500 Series reduces individual differences in impression dimension measurement in the Vickers hardness test by adopting special image analysis technologies. In addition, improved precision and high speed have been realized with a detecting time of 0.3 seconds.




SPECIFICATIONS

Model No.	AAV-503	AAV-504
Order No.*	810-727A	810-728A
Test force range	1.961 - 196.1N (200gf - 20kgf)	9.807 - 490.3N (1kgf - 50kgf)
Test force switching	Manual	Manual
Objective	10X / 20X	10X / 20X
Measurable indentation size	40 - 400 / 20 - 100 μ m	40 - 400 / 20 - 100 μ m
Minimum reading	0.1 μ m	0.1 μ m

* PC is optional

System Configuration



Technical Data

Automatic indication detection
 Detecting reproducibility: $\pm 0.5\%$ (0.1 μ m)
 Detecting method: Quadratic curve regression method
 Detecting time: 0.3 seconds
 Detecting minimum unit: 0.1 μ m
 Manual measurement function: Measurement method with video line
 X-Y automatic stage
 Stage area: 130 x 130mm
 Movement range: 50 x 50mm
 Minimum pitch: 1 μ m
 Software function
 Patterned measurement: Line, staggered, 3-point staggered, matrix, circle, arc, random
 Teaching measurement pattern setting
 Hardness calculation function
 Hardness conversion function
 OK/NG judgment
 Analysis software function:
 Device condition display
 Measurement data display
 Statistical calculation
 Graph display
 Dimensions (W x D x H) / Mass
 AAV-503 / AAV-504: 665 x 516 x 1000mm / 91kg

Optional Accessory

PC System

MZT-500



SERIES 810 — Micro Zone Test System

FEATURES

When it comes to evaluating mechanical properties of ultra-small regions of ultra-fine specimens, the MZT-500 Series models are exceptionally powerful tools in the fields of research and development and quality control. The MZT-500 can evaluate mechanical properties, which conventional

hardness testing machines for fine specimens cannot measure, such as various CVD and PVD-deposited or generated films, including ion-plated films; hardness of ultra-fine cross-sections; bonding mechanical properties; and mechanical wear properties of carbon fibers, glass fibers, whiskers, etc.

- Test data
The indentation factor can be obtained, which is related to the hardness value (partially) shown in Martens hardness test (ISO14577) and Young's modulus. Deformation characteristics in the load, dwell, and unload phases are also obtainable for use in determining properties of the specimen material.
- Hardness tests such as Vickers and Knoop hardness tests are supported.
- The balance lever vibration isolation mechanism reduces the effect of external vibrations on measurements.
- Indenter indentation depth can be measured up to a maximum of 20 μ m with a resolution of 0.1nm.
- Test forces between 0.1mN and 1000mN can be applied electromagnetically for evaluation of material properties in submicroscopic areas.
- Field-compatible form with cover for protection against dust and wind.



SPECIFICATIONS

Model No.	MZT-500L	MZT-500P
Order No.	810-813A	810-814A
Basic system	✓	✓
Data analysis / control device	✓	✓
Manual type XY stage (Travel range 25x25mm)	✓	—
Automatic XY stage (Travel range: 50x50mm)	—	✓

Test force loading device	Test force range: 0.1 to 1000mN
	Control resolution: 0.916 μ N
	Loading speed: 0.01 to 100mN/s
Indentation depth measurement	Range: 0 to 20 μ m
	Resolution: 0.1nm
Indenter	Type: Bercovich triangular pyramid indenter
Sample surface observation method	Camera: 1/3 inch black and white (410,000 pixels)
	Objective (monitor magnification): 100X (2500X), Optional: 10X (250X), 40X (1000X)
	Maximum height: 90mm
Specimen dimensions	Maximum depth: 90mm (From the center of the indenter axis)
	Indentation test (with preliminary test force)
Test type	Indentation test (without preliminary test force)
	Indentation depth setting test, continuous indentation test, repeated indentation test

HV-112 / 113 / 114 / 115

SERIES 810 — Vickers Hardness Testing Machines

FEATURES

- A wide range of test forces from 1.961N to 490.3N* (.2kgf - 50kgf) is available for measuring a wide variety of specimens. The load duration can be set in 1sec increments between 5 and 99sec. The minimum reading of indentation is 0.1µm. It allows small indentations to be measured with high precision.

Function: Control unit

- Back-lit LCD graphic display for Indentation size (D1 and D2), Hardness value and scale, Number of measurement point Test conditions (HV / HK indenter type, test force, load duration), GO / ±NG tolerance judgment, Cylindrical and spherical surface compensation and offset
- Remote control of power turret
- Conversion to other hardness scales
- Statistical processing



HV-112, HV-114



HV-113, HV-115

SPECIFICATIONS

Model	HV112	HV113	HV114	HV115
Order No.	810-163A	810-981A	810-165A	810-985A
Test force	1.961N (0.2kgf), 2.942N (0.3kgf), 4.903N (0.5kgf), 9.807N (1kgf), 24.51N (2.5kgf), 49.03N (5kgf), 98.07N (10kgf), 196.1N (20kgf)		9.807N (1kgf), 19.61N (2kgf), 29.42N (3kgf), 49.03N (5kgf), 98.07N (10kgf), 196.1N (20kgf), 294.2N (30kgf), 490.3N (50kgf)	
Test force selection	Dial			
Loading accuracy	±1%			
Load control	50 - 100µ/s Automatic (loading, duration, unloading) Automatic			
Load rate	5~99 sec.			
Objective lenses	10X, 20X			
Measuring microscope	100X / 200X		100X / 200X	
Total magnification	—			
Measuring range	350, 700µm		350, 700mm	
Minimum reading	0.1µm			
Video monitor	—		—	
Camera	—		—	
Display	—		—	
Display	—		9" monochrome CRT	
Total magnification	—		—	
Total magnification	—		250X, 500X	
Monitoring range	—		—	
Monitoring range	—		520 x 670µm, 260 x 330µm	
Measuring range	—		—	
Measuring range	—		410 x 570µm, 200 x 280µm	
Display Function	Conversion: Hard: TENS, HS, HBS, HR15N, HR30N, HR45N, HRA, HRD, HRC, HK, HV, Soft: TENS, HR15T, HR30T, HR45T, HRA, HRF, HRB, HRG, HK, HV, Statistical list; N, Max., Min., Average, Range, High, Low, Good, Over, Under, SD(n-1), SD(n-1), SD(n) OK/NG Judgement, Curve correction; 0.01 to 200.00mm			
Specimen	8.07" (205mm) or Flat anvil			
Maximum height	8.07" (205mm) or Flat anvil			
Maximum depth	6.7" (170mm) from center of indenter shaft			
Optical path	2-way switchable (microscope/photograph)			
Output	SPC, RS-232C Centronics			
Power supply	120V AC (±10%) 60Hz			
Dimensions (WxDxH)	9.7" x 20.3" x 31.3" (245 x 515 x 770mm)			
Main Unit only	9.7" x 20.3" x 31.3" (245 x 515 x 770mm)			
Mass	110 lbs. (50kg)	121.4 lbs. (55.2kg)	110 lbs. (50kg)	121.4 lbs. (55.2kg)

* 7.48" (190mm) if using 50 x 50mm-travel XY stage (No. 810-012).


Technical Data

- Motorized lens turret
- Adjustable loading rate

Optional Accessories

- 19BAA011: Hardness test block (200HV)
- 19BAA012: Hardness test block (300HV)
- 19BAA013: Hardness test block (400HV)
- 19BAA014: Hardness test block (500HV)
- 19BAA015: Hardness test block (600HV)
- 19BAA016: Hardness test block (700HV)
- 19BAA017: Hardness test block (800HV)
- 19BAA018: Hardness test block (900HV)

50x50mm travel stage



Dimensions: 4.92x4.92" (125x125mm)

Minimum reading: 0.01mm

810-012


Consumable Parts

- 513667: Illumination lamp (1 pc.)

Optional Accessories

Micro-Vickers/Vickers Hardness Testing Machine

Clamping devices (Vises)




Vise

Max. opening: 3.94" (100mm)

810-017

Rotary Table



Rotary Table

810-018


Round Tables



Dimensions: 8" (203mm)

810-037-7


Specimen (thin plate) Holder



Secures a plate with a thickness of .197" (5mm) or less, or foil-like specimens.

810-013


Specimen (wire) Holder



Used to horizontally secure a wire or needle specimen that has a diameter of .126" (3.2mm) or less.

810-014

Specimen (wire or ball) Holder



Used to vertically secure a wire or ball specimen that has a diameter of .126" (3.2mm) or less.

810-015

Test Blocks

Order No.	Description	Load
64BAA173	Vickers 100HV Test Block	100gf
64BAA174	Vickers 200HV Test Block	100gf
64BAA175	Vickers 300HV Test Block	100gf
64BAA176	Vickers 400HV Test Block	100gf
64BAA177	Vickers 500HV Test Block	100gf
64BAA178	Vickers 600HV Test Block	100gf
64BAA179	Vickers 700HV Test Block	100gf
64BAA180	Vickers 800HV Test Block	100gf
64BAA181	Vickers 900HV Test Block	100gf
64BAA182	Vickers 100HV Test Block	500gf
64BAA183	Vickers 200HV Test Block	500gf
64BAA184	Vickers 300HV Test Block	500gf
64BAA185	Vickers 400HV Test Block	500gf
64BAA186	Vickers 500HV Test Block	500gf
64BAA187	Vickers 600HV Test Block	500gf
64BAA188	Vickers 700HV Test Block	500gf
64BAA189	Vickers 800HV Test Block	500gf
64BAA190	Vickers 900HV Test Block	500gf
64BAA191	Vickers 100HV Test Block	1000gf
64BAA192	Vickers 200HV Test Block	1000gf
64BAA193	Vickers 300HV Test Block	1000gf
64BAA194	Vickers 400HV Test Block	1000gf
64BAA195	Vickers 500HV Test Block	1000gf
64BAA196	Vickers 600HV Test Block	1000gf
64BAA197	Vickers 700HV Test Block	1000gf
64BAA198	Vickers 800HV Test Block	1000gf
64BAA199	Vickers 900HV Test Block	1000gf
64BAA200	Knoop 200HK Test Block	100gf
64BAA201	Knoop 300HK Test Block	100gf
64BAA202	Knoop 400HK Test Block	100gf
64BAA203	Knoop 500HK Test Block	100gf
64BAA204	Knoop 600HK Test Block	100gf
64BAA205	Knoop 700HK Test Block	100gf
64BAA206	Knoop 800HK Test Block	100gf
64BAA207	Knoop 250HK Test Block	500gf
64BAA208	Knoop 300HK Test Block	500gf
64BAA209	Knoop 400HK Test Block	500gf
64BAA210	Knoop 500HK Test Block	500gf
64BAA211	Knoop 600HK Test Block	500gf
64BAA212	Knoop 700HK Test Block	500gf
64BAA213	Knoop 800HK Test Block	500gf
64BAA214	Knoop 250HK Test Block	1000gf
64BAA215	Knoop 300HK Test Block	1000gf
64BAA216	Knoop 400HK Test Block	1000gf
64BAA217	Knoop 500HK Test Block	1000gf
64BAA218	Knoop 600HK Test Block	1000gf
64BAA219	Knoop 700HK Test Block	1000gf
64BAA220	Knoop 800HK Test Block	1000gf

*other hardness ranges and test forces available


Bulbs

Order No.	Description
513667	Bulb, 12v/50w, halogen double pin type, HM series with box style illuminators.
19BAA219	Bulb, 6v/2 0w, halogen double pin type, Later H series
19BAA095	Bulb, 6v/15w, halogen bayonet type, all E, G and early H series testers.

Indenters

Order No.	Type	Model
19BAA061	Knoop Indenter	H, HM Standard Series
19BAA058	Vickers Indenter	H, HM Standard Series
19BAA062	Knoop Indenter	MVK-H2, H3, HM114, HM220
19BAA059	Vickers Indenter	MVK-H2, H3, HM114, HM220
19BAA060	Vickers Indenter	HV, AVK-C Series


Universal Specimen Holder



Used to secure a specimen, that has a measuring surface that is hard to stabilize, perpendicular to the indenter axis.

810-020

50x50mm travel stage




Dimensions: 4.92x4.92" (125x125mm)

Minimum reading: 0.01mm

810-012

Clamping devices (Vises)



Vise

Max. opening: 1.77" (45mm)

Standard for the HM 100 series.

810-016

Rockwell hardness scales

Preliminary test force: 98.07N (10kgf)

Scale	Indenter	Test force	Applications
A	Diamond	588.4N(60kgf)	Cemented carbide, thin steel plates case hardened steel
D		980.7N(100kgf)	
C		1471N(150kgf)	
F	1/16" diameter steel ball	588.4N(60kgf)	Bearing metal, copper, annealed steel, brass, hard-drawn aluminum alloys beryllium copper, phosphor bronze
B		980.7N(100kgf)	
G		1471N(150kgf)	
H	1/8" diameter steel ball	588.4N(60kgf)	Bearing metal
E		980.7N(100kgf)	
K		1471N(150kgf)	
L	1/4" diameter steel ball	588.4N(60kgf)	Plastics, lead
M		980.7N(100kgf)	
P		1471N(150kgf)	
R	1/2" diameter steel ball	588.4N(60kgf)	Plastics
S		980.7N(100kgf)	
V		1471N(150kgf)	

Hardness and Hardness Measurement

Hardness is a measure of resistance of a material to deformation when an external force or load is applied to the material. There are several hardness scales, which use different methods of applying force and quantifying the resistance to deformation. Hardness is closely correlated to other mechanical characteristics. It is, like many other mechanical characteristics, a relative value that has no fundamental quantity or absolute standard and is different from physical quantities such as length, time, and force. Because of this, hardness values are determined using a standard testing machine under standard conditions.

Today the most popular hardness scales are Brinell hardness (HB), Vickers hardness (HV), Rockwell and Rockwell superficial hardness (HR) and Knoop hardness (HK). Most hardness tests determine hardness from the area of the indentation made in a specimen by the indenter under a known load. The Brinell test was devised in Sweden, the Vickers test in the United Kingdom, and the other hardness tests in the United States. Although hardness is a relative value, Brinell, Vickers, and Knoop hardness are expressed in a unit of stress (1 kgf/mm² or 9.8MPa).

Rockwell Superficial hardness scales

Preliminary test force: 29.42N (3kgf)

Scale	Indenter	Test force	Applications
15N	Diamond	147.1N(15kgf)	Carburized layer, sintered
30N		294.2N(30kgf)	
45N		441.3N(45kgf)	
15T	1/16" diameter steel ball	147.1N(15kgf)	Thin copper plates (brass, bronze), mild steel
30T		294.2N(30kgf)	
45T		441.3N(45kgf)	
15W	1/8" diameter steel ball	147.1N(15kgf)	Plastics, zinc, bearing alloys
30W		294.2N(30kgf)	
45W		441.3N(45kgf)	
15X	1/4" diameter steel ball	147.1N(15kgf)	Plastics, zinc, bearing alloys
30X		294.2N(30kgf)	
45X		441.3N(45kgf)	
15Y	1/2" diameter steel ball	147.1N(15kgf)	Plastics, zinc, bearing alloys
30Y		294.2N(30kgf)	
45Y		441.3N(45kgf)	

Rockwell Hardness and Rockwell Superficial Hardness

In the Rockwell hardness and the Rockwell superficial hardness tests, a conical diamond indenter with a 120° angle and a radius of curvature of 0.2mm, or a steel or carbide ball indenter is pressed into the specimen. First, a preliminary test force is applied, then a total test force is applied, and then the test load is reduced to the preliminary test force. The hardness number is determined from the difference, h, of the indentation depth of the indenter between the first and second applications of the preliminary test force.

The Rockwell hardness test uses a preliminary load of 10kgf, and the Rockwell superficial hardness test uses a preliminary test force of 3kgf. The Rockwell and Rockwell superficial hardness have multiple scales to indicate specific combinations of the indenter type, test force, and formula to obtain the hardness. A unique symbol is given to each scale.

Minimum Thickness Chart

Thicker or harder material can be tested.	Rockwell Superficial Hardness Scales			Rockwell Regular Hardness Scales		
Thickness inches (mm)	15N	30N	45N	A	D	C
.006 (0.15)	92	•	•	•	•	•
.008 (0.20)	90	•	•	•	•	•
.010 (0.25)	88	•	•	•	•	•
.012 (0.30)	83	82	77	•	•	•
.014 (0.36)	76	78.5	74	•	•	•
.016 (0.41)	68	74	72	86	•	•
.018 (0.46)	√	66	68	84	•	•
.020 (0.51)	√	57	63	82	77	•
.022 (0.56)	√	47	58	79	75	69
.024 (0.61)	√	√	51	76	72	67
.026 (0.66)	√	√	37	71	68	65
.028 (0.71)	√	√	20	67	63	62
.030 (0.76)	√	√	√	60	58	57
.032 (0.81)	√	√	√	√	51	52
.034 (0.86)	√	√	√	√	43	45
.036 (0.91)	√	√	√	√	√	37
.038 (0.96)	√	√	√	√	√	28
.040 (1.02)	√	√	√	√	√	20

Thicker or harder material can be tested.	Rockwell Superficial Hardness Scales			Rockwell Regular Hardness Scales		
Thickness inches (mm)	15T	30T	45T	F	B	G
.010 (0.25)	91	•	•	•	•	•
.012 (0.30)	86	•	•	•	•	•
.014 (0.36)	81	80	•	•	•	•
.016 (0.41)	75	72	71	•	•	•
.018 (0.46)	68	64	62	•	•	•
.020 (0.51)	√	55	53	•	•	•
.022 (0.56)	√	45	43	•	•	•
.024 (0.61)	√	34	31	98	94	94
.026 (0.66)	√	√	18	91	87	87
.028 (0.71)	√	√	4	85	80	76
.030 (0.76)	√	√	√	77	71	68
.032 (0.81)	√	√	√	69	62	59
.034 (0.86)	√	√	√	√	52	50
.036 (0.91)	√	√	√	√	40	42
.038 (0.96)	√	√	√	√	28	31
.040 (1.02)	√	√	√	√	√	22

√ - Can be tested - no minimum hardness.

HR-521(L) / 523(L)



SERIES 810 — Rockwell Type Hardness Testing Machines

Technical Data

Preliminary test force:	29.42N, 98.07N
Test force	
Rockwell superficial:	147.1, 294.2, 441.3N
Rockwell:	588.4, 980.7, 1471N
Brinell*:	
Test force setting:	By control unit
Load control:	Automatic (loading, duration, unloading)
Load duration:	0s - 120s (1s increments)
Max. specimen height:	205mm (for standard flat anvil)
Max. specimen depth:	150mm (from the center of indenter shaft)
Stage elevation:	Manual or power drive
Control unit:	Sheetswitch type or touch screen type
Data output:	RS-232C, Digimatic code (SPC) and Centronics
Power supply:	120V AC, 50/60Hz
Dimensions (W x D x H)	
Main unit:	250 x 670 x 605mm
Control unit:	165 x 260 x 105mm

Optional Accessories: See page K-13, 14

Various shapes of specimen can be measured.
(Nose-type indenter axis mechanism has been adopted)
The nose-type indenter mechanism allows measurement of pipe samples as well as the top surface of a flat sample.



Function: Touch screen type

- Touch screen operation with a back-lit LCD graphic display.
- Remote selection of the test force linked to the hardness scale selection.
- Choice of message language in English, German, French, Spanish, Italian and Japanese for user friendly operation.
- Cylindrical and spherical surface compensation.
- Data offset
- Conversion to other hardness scales.
- Powerful statistical processing with flexible data point editing and 1024 data memory.
- Measured data editing
- OK/NG tolerance judgment.
- Statistical processing, histogram and X-R chart

FEATURES

- Multiple test force generation for Rockwell, Rockwell Superficial and Brinell hardness.
- Dolphin-nose indenter arm for easy reach of interior (min. $\varnothing 40\text{mm}/\varnothing 22\text{mm}^*$) and exterior surfaces.
*When using an optional diamond indenter (19BA292).
- Real time electronic test force control for accurate loading. This perfectly eliminates load force overshooting.
- Indenter escape function for continuous testing at fixed table position. This eliminates instability caused by the table retraction.
- Auto-stop elevation table and automatic preliminary test force loading to provide stable test force generation.



SPECIFICATIONS

Model	HR-521	HR521L	HR-523	HR-523L
Order No.	810-202-03A	810-205-03A	810-204-03A	810-207-03A
Preliminary Test Force	29.42N (3kgf), 98.07N (10kgf)			
Test Force	Rockwell 588.4N (60kgf), 980.7N (100kgf), 1471N (150kgf)			
	Rockwell Superficial 147.1N (15kgf), 294.2N (30kgf), 441.3N (45kgf)			
	Brinell 1839N (187.5kgf) (for use with 2.5mm ball)			
Force Control	Automatic control (unloading/duration/unloading) with closed loop feed back			
Console/Display Unit	Touch screen operation with back-lit LCD graphic display			
Test Force Selection	By touch screen			
Table up/down drive	Manual (w/Auto-brake mechanism)		Power-Drive (for full-automatic measurement)	
Load Duration	0 to 120 sec. (1 sec. step)			
Maximum Specimen Height	8.1" (205mm)	15.5" (395mm)	8.1" (205mm)	15.5" (395mm)
Maximum Specimen Depth	5.9" (150mm)			
Display Indication Functions	Hardness value, Converted hardness value, Test conditions, OK/NG tolerance judgement, statistical processing result Rockwell/Rockwell superficial hardness testing. Continuous testing. Cylindrical/spherical surface compensation, data offset Hardness conversion (HV, HK, HRA/B/C/D/F/G/15T/30T/45T/15N/30N/45N, HS, HB, HBW, tensile strength) OK/NG tolerance judgement, measured data editing, data memory (max 1024 data) SPC calculation (No. of data, max/min/mean values, range, upper/lower limit values, standard deviation, No. of passing/defective) Histogram, X-R chart			
Data Output	RS-232C, SPC, Centronics			
Dimensions (W x D x H)	9.84" x 26.38" x 23.82" (250 x 670 x 605mm)			
Mass	60kg			

HR-210MR/320MS/430MR/430MS

SERIES 963 — Rockwell Hardness Testing Machines

FEATURES

- The new frame design allows the full 7.1" of specimen capacity without the need to cut a whole in the table.
- Simple to operate; the Dial Type HR210 features an automatic zero reset. The digital HR320 model uses a flashing bar graph to indicate when the initial test force has been reached.
- Automatic brake and automatic start function that prevents overloading and begins test cycle. The HR430 model also includes the dial a weight system for easier load selection.
- All models are complete with Flat and VEE anvils, diamond and 1/6" carbide ball indenters, 2 HRC and 1 HRBW Rockwell blocks (MR models) or 3 Rockwell blocks and an HR30N and HR30TW for MS testers.



HR-210MR
Rockwell hardness testing machine
Motorized Loading
Motor drive - Button start model



HR-320MS
Rockwell/Rockwell Superficial hardness testing machine
Motorized Loading
Motor drive - Button start model



HR-430MR
Rockwell hardness testing machine
Motorized Loading
Motor drive - Automatic start model



HR-430MS
Rockwell/Rockwell Superficial hardness testing machine
Motorized Loading
Motor drive - Automatic start model

Technical Data

Preliminary test force: 29.42N*, 98.07N
 Test force
 Rockwell superficial*: 147.1, 294.2, 441.3N
 Rockwell: 588.4, 980.7, 1471N
 Test force setting: By dial
 Load control: Automatic (loading, duration, unloading)
 Anvil: Flat (ø64mm)
 Max. specimen height: 7.1" / 180mm
 Max. specimen depth: 6.5" / 165mm (from the center of indenter shaft)
 Stage elevation: Manual
 Data output*: RS-232C, Digimatic code (SPC)
 Power supply: 120V AC, 50/60Hz

*HR320-430 only

SPECIFICATIONS

Order Number	963-220-10A	963-231-10A	963-240-10A	963-241-10A
Model	HR-210MR	HR-320MS	HR-430MR	HR-430MS
Test Scales	Rockwell	Rockwell and Rockwell Superficial	Rockwell	Rockwell and Rockwell Superficial
Standard	JIS B 7726 ISO 6508-2 ASTM E18-10			
Preliminary Test Force	98.07N (10kgf)	98.07N (10kgf), 29.42 (3kgf)	98.07N (10kgf), 29.42 (3kgf)	98.07N (10kgf), 29.42 (3kgf)
Test Force Rockwell	588.4N (60kgf), 980.7N (100kgf), 1471N (150kgf)			
Test Force Superficial	—	147.1N (15kgf), 294.2N (30kgf), 441.3N (45kgf)	—	147.1N (15kgf), 294.2N (30kgf), 441.3N (45kgf)
Display	Dial	Matrix Backlight LCD		
Hardness Minimum Value	0.5 HR	0.1 HR		
Scale Conversions	—	HRC, HRB, HV, HBW, HS, Mpa plus offset, OK/NG		
Preliminary Test Force	Manual (with automatic zero set)	Manual (with Loading Navigator)	Manual (with automatic brake-start)	
Total Test Force Control	Automatic (loading, duration, unloading)			
Loading Method	Dead Weight			
Load Duration (Dwell)	Fixed (3s to 5.5s) or Manual	Adjustable (1s to 99s) or Manual		
Maximum Specimen Ht.	7.1" (180mm)			
Maximum Depth	6.5" (165mm)			
Data Output	—	RS-232C, SPC		
Power Supply	120V AC (±10%), 60Hz			
Dimensions (D x W x H)	20.15"(512mm) x 9.25"(235mm) x 30.7"(780mm)	20.6"(523mm) x 9.25"(235mm) x 30.7"(780mm)	20.6"(523mm) x 9.25"(235mm) x 30.7"(780mm)	20.6"(523mm) x 9.25"(235mm) x 30.7"(780mm)
Mass	100.53lb (45.6kg)	102.07lb (46.3kg)	108.69lb (49.3kg)	110.01lb (49.9kg)

Optional Accessories


For Rockwell/Rockwell Superficial Type Hardness Testing machine



Calibration Set

Order No.	Order No.
64BAA241	64BAA242
C Scale Set	B Scale Set
Test Blocks	Test Blocks
64BAA125	64BAA126
64BAA124	64BAA132
64BAA158	64BAA135
Indenter	Indenter
64BAA072	64BAA078
Order No.	Order No.
64BAA243	64BAA244
30N Scale Set	30T Scale Set
Test Blocks	Test Blocks
64BAA128	64BAA129
64BAA165	64BAA140
64BAA167	64BAA130
Indenter	Indenter
64BAA073	64BAA078

Rockwell Type Diamond Indenters



Order No.	Scale
64BAA072	C
64BAA073	N
64BAA086	A
64BAA071	C & N

Order No.	Hardness
64BAA159	HRA81/86 Rockwell Test Block
64BAA160	HRA75/79 Rockwell Test Block
64BAA161	HRA70/73 Rockwell Test Block
64BAA162	HRA65/68 Rockwell Test Block
64BAA163	HRA60/62 Rockwell Test Block
64BAA249	HRBW95/100 Rockwell Test Block
64BAA126	HRBW90/95 Rockwell Test Block
64BAA131	HRBW80/85 Rockwell Test Block
64BAA132	HRBW70/75 Rockwell Test Block
64BAA133	HRBW60/65 Rockwell Test Block
64BAA134	HRBW50/55 Rockwell Test Block
64BAA135	HRBW40/45 Rockwell Test Block
64BAA127	HRBW30/35 Rockwell Test Block
64BAA136	HRBW20/25 Rockwell Test Block
64BAA137	HRBW10/15 Rockwell Test Block
64BAA138	HRBW0/5 Rockwell Test Block
64BAA125	HRC60/65 Rockwell Test Block
64BAA157	HRC50/55 Rockwell Test Block
64BAA124	HRC40/45 Rockwell Test Block
64BAA123	HRC30/35 Rockwell Test Block
64BAA158	HRC20/25 Rockwell Test Block
Order No.	Hardness
64BAA129	HR30T74/79 Rockwell Test Block
64BAA139	HR30T70/73 Rockwell Test Block
64BAA140	HR30T63/67 Rockwell Test Block
64BAA141	HR30T56/60 Rockwell Test Block
64BAA142	HR30T49/53 Rockwell Test Block
64BAA130	HR30T43/47 Rockwell Test Block
64BAA143	HR30T36/39 Rockwell Test Block
64BAA144	HR30T29/33 Rockwell Test Block
64BAA145	HR30T22/26 Rockwell Test Block
64BAA146	HR30T15/18 Rockwell Test Block
64BAA147	HR15T90/92 Rockwell Test Block
64BAA148	HR15T86/69 Rockwell Test Block
64BAA149	HR15T83/85 Rockwell Test Block
64BAA150	HR15T80/82 Rockwell Test Block
64BAA151	HR15T77/79 Rockwell Test Block
64BAA152	HR15T72/74 Rockwell Test Block
64BAA153	HR15T70/72 Rockwell Test Block
64BAA154	HR15T68/69 Rockwell Test Block
64BAA155	HR15T64/66 Rockwell Test Block
64BAA156	HR15T61/63 Rockwell Test Block

Order No.	Hardness
64BAA222	HR45N65/70 Rockwell Test Block
64BAA223	HR45N55/60 Rockwell Test Block
64BAA224	HR45N45/50 Rockwell Test Block
64BAA225	HR45N35/40 Rockwell Test Block
64BAA226	HR45N25/30 Rockwell Test Block
64BAA128	HR30N77/82 Rockwell Test Block
64BAA164	HR30N68/73 Rockwell Test Block
64BAA165	HR30N59/64 Rockwell Test Block
64BAA166	HR30N50/55 Rockwell Test Block
64BAA167	HR30N40/45 Rockwell Test Block
64BAA168	HR15N90/93 Rockwell Test Block
64BAA169	HR15N85/88 Rockwell Test Block
64BAA170	HR15N80/83 Rockwell Test Block
64BAA171	HR15N75/77 Rockwell Test Block
64BAA172	HR15N69/72 Rockwell Test Block

Carbide Ball Indenters

Order No.	Description
19BAA515	1/16" Carbide ball indenter
19BAA504	1/8" Carbide ball indenter
19BAA505	1/4" Carbide ball indenter
19BAA506	1/2" Carbide ball indenter
19BAA507	1/16" Carbide ball (1pc.)
19BAA508	1/8" Carbide ball (1pc.)
19BAA509	1/4" Carbide ball (1pc.)
19BAA510	1/2" Carbide ball (1pc.)


Steel Ball Indenters

Order No.	Description
64BAA074	1/16" diameter steel ball indenter
19BAA078	1/16" diameter steel ball indenter (auto-discrimination type)
64BAA075	1/8" diameter steel ball indenter
19BAA079	1/8" diameter steel ball indenter (auto-discrimination type)
64BAA076	1/4" diameter steel ball indenter
19BAA080	1/4" diameter steel ball indenter (auto-discrimination type)
64BAA077	1/2" diameter steel ball indenter
19BAA081	1/2" diameter steel ball indenter (auto-discrimination type)
64BAA082	1/16" diameter spare steel ball (10 pcs)
64BAA083	1/8" diameter spare steel ball (10 pcs)
64BAA084	1/4" diameter spare steel ball (10 pcs)
64BAA085	1/2" diameter spare steel ball (10 pcs)

Optional Accessories

For Rockwell/Rockwell Superficial Type Hardness Testing machine

Flat anvil




Diameter: 2.5" (64mm)

810-039-7

Diameter: 1.5" (38mm)

810-039-8


Round Table



Diameter: 8" (203mm)

810-037-7

Spot anvils



Diameter: .25" (6.4mm)

Height: .88" (22mm)

810-044-7



Diamond-tipped type for
Rockwell superficial hardness measurement

810-030-7

V-anvils



Diameter: 1.5" (38mm)

Groove width: .38" (9.7mm)

810-041-7



Diameter: 1.5" (38mm)

Groove width: 1.5" (38mm)

810-040-7



Diameter: .38" (9.7mm)

Groove width: .38" (9.7mm)


810-042-7

Adjustable support

Adjustable height:
13 to 18.5" (330 to 470mm)

Used to mount a V-anvil.

810-028-7



264-504-5A



937386



Optional Accessories

937387: SPC cable (40"/1m)

06ADV580E: USB input tool

Reference page A-12 for specifications

Hardmatic HH-411

SERIES 810 — Impact Type Hardness Testing Unit

Technical Data

Impactor:	Impact hammer with integrated detector and carbide-ball tip (D type: conforming to ASTM A 956)
Display unit:	7-segment LCD
Functions:	Auto angle compensation, Offset, OK/NG judgment, Hardness scale conversion Data storage (1800 data entries) Statistical analysis (Average, Maximum, Minimum, Dispersion) Auto sleep function Impact counter display function
Testable workpiece	
Thickness:	Minimum 5mm or more
Mass:	5kg or more in mass
Test points:	5mm or more from the edge of the sample, 3mm or more to each of the tested points.
Surface roughness:	Ra 10µm or less
Power supply:	Alkaline AA battery 2pcs or optional AC adapter (battery life: 70 hours)

Standard Accessories

19BAA265	Test Block HLD800
810-291	Display Unit
810-287	Detector
19BAA460	Cable
	Battery AA (Alkaline) 2pcs.

Optional Accessories

264-504-5A:	Digimatic Mini-Processor DP-1VR
937387:	Connecting cable for
09EAA082:	Printer paper (10 rolls/set)
810-622A:	Thermal printer DUP-414
19BAA262:	Thermal printer connecting cable
19BAA157:	Thermal printer paper
19BAA238:	RS-232C connecting cable for PC
06AEG302JA:	AC adapter of display unit
19BAA243:	Hardness test block (880HLD)
19BAA244:	Hardness test block (830HLD)
19BAA245:	Hardness test block (730HLD)
19BAA246:	Hardness test block (620HLD)
19BAA247:	Hardness test block (520HLD)
19BAA248:	Support ring for convex surface of cylinder (R10 - R20)
19BAA249:	Support ring for convex surface of cylinder (R14 - R20)
19BAA250:	Support ring for convex surface of sphere (R10 - R27.5)
19BAA251:	Support ring for concave surface of sphere (R13.5 - R20)
19BAA457:	Carbide ball for D, DC, D+15 type impactors
19BAA458:	Ball shaft for DL type impactor
810-287:	D type impactor UD-411
810-288:	DC type impactor UD-412
810-289:	D+15 type impactor UD-413
810-290:	DL type impactor UD-414

HH-411 is a rebound type portable hardness tester for metal with a compact body and high operability. It allows anyone to perform hardness testing easily at the touch of a key, so it can be used widely on various components in the field.



810-298: ASTM standard
Including the display unit, D type impactor (810-287) and carbide ball (19BAA457).

SPECIFICATIONS

Model	HH-411		
Order No.	810-298		
Hardness Range	L-Value (ASTM A956)		
Detector	Input device D (carbide ball)		
Display	Hardness	Range	Resolution
	HL	1-999 HL	1 HL
	HV	43-950 HV	1 HV
	HB	20-894 HB	1 HB
	HRC	19.3-68.2 HRC	0.1 HRC
	HRB	13.5 - 101.7 HRB	0.1 HRB
	HS	13.2 - 99.3 HS	0.1 HS
	HTN	499 - 1996 Mpa	1 Mpa
Functions	Conversions: HL, HV, HB, HRC, HRB, HS, HTN Judgment: OK/NG Offsetting Memory: 1,800 data		
Indentation Direction	Any direction		
Output	RS-232C, SPC		
Power supply	Alkaline AA Battery 2pcs.		
Dimensions	Detector: (Dia. X H) 1.10" x 6.89" (28 x 175mm) Display: (W x D x H) 2.76" x 4.33" x 1.38" (70 x 110 x 35mm)		
Mass	Detector: .26lbs (120g) Display: .44lbs (200g)		

Impactors (Optional accessories)

Various impactors can be connected to the display unit.



810-288
Use for inner walls of cylinders.
The grip is short to allow easy positioning within a cylinder.



810-290
Use for gear teeth, welded corners, etc.



810-289
Use for concave workpieces such as gear teeth, ball bearing races, etc.

Hardmatic HH-300

SERIES 811 — Durometers for Rubber and Plastics Hardness Testing

FEATURES

Digital / Dial Durometers are suitable for testing the nature of the following materials — natural rubber, neoprene, polyesters, P.V.C., leather, nitrile rubber, wax, vinyl, cellulose acetates, glass polystyrene, etc.



SPECIFICATIONS

Order No.	Digital	811-330	811-336	811-336-01	811-332	811-338	811-338-01	811-334
	Dial	811-329	811-335	811-335-01	811-331	811-337	811-337-01	811-333
Model No.	Digital	HH-330	HH-336	HH-336-01	HH-332	HH-338	HH-338-01	HH-334
	Dial	HH-329	HH-335	HH-335-01	HH-331	HH-337	HH-337-01	HH-333
Scale		Shore E	Shore A			Shore D		
Applications		Soft Rubber, Sponge, Felt, Hard Foam	Natural rubber, soft elastomers, etc.			Hard elastomers, plastics, hard rubber, ebonite, etc.		
Resolution		0.5 (digital) or 1 (dial)					0.5 (digital) or 1 (dial)	
Range		HA: 10 - 90					HD: 20 - 90	
Standards	ASTM D 2240	—	✓	✓	—	✓	✓	—
	ISO 868	—	✓	✓	—	✓	✓	—
	ISO 7619	—	✓	✓	—	✓	✓	—
	DIN 53 505	—	—	✓	—	—	✓	—
	JIS K 6253	✓	✓	✓	—	✓	✓	—
	JIS K 7215	—	✓	✓	—	✓	✓	—
Pressure foot		44 x 18mm	44 x 18mm ø18mm			44 x 18mm ø18mm		—
Spring force (mN)		WE=550+HE	WA=550+75HD (HA:Reading 10-90)			WD=444.5HD (HD:Reading 20-90)		—
Indenter		Sphere (Tip diameter: 0.79mm)	Blunt taper (Tip diameter: 0.79mm)			Sharp point (Tip curvature: 0.1±0.01mm)		—
Tip angle		35°±0.25°				30°±0.5°		—
Indenter diameter		1.25mm						
Indenter protrusion		2.5mm						
Functions		Digital: Data hold, Zero -setting, SPC output, Power ON/OFF (Power supply: SR44 x 1pc.) Analog Durometer: Peak retaining hand						
Type		Compact	Compact	Long-leg	Compact	Compact	Long-leg	—
Dimensions (WxDxH)	Digital	60 x 28.5 x 151	60 x 28.5 x 151mm		60 x 28.5 x 193mm	60 x 28.5 x 151mm		60 x 28.5 x 193mm
	Dial	56 x 33.5 x 144mm	56 x 33.5 x 144mm		56 x 33.5 x 186mm	56 x 33.5 x 144mm		56 x 33.5 x 186mm
Mass	Digital	290g	290g	310g	290g	290g	310g	—
	Dial	300g	300g	320g	300g	300g	320g	—

Technical Data

- Designed in accordance with the ASTM D 2240, ISO868, ISO 7619, DIN 53 505, JIS K 6253, and JIS K 7215 specifications.
- Units are available in both Shore A and Shore D scales, and will test a wide variety of applications.
- The Digital Durometer is provided with data hold function, permitting the operator to make an error-free reading on the LCD screen.
- The Dial Durometer is provided with a peak retaining hand for error-free reading.

Testing stand applications

These stands are used to mount Durometers. They allow constant-pressure hardness measurement by pressing the Durometer vertically on a workpiece.

- Anyone can perform repeatable hardness measurement due to fewer possibilities of human error and measurement variations.
- The supplied weights can be attached directly to a Durometer and allow constant-pressure hardness measurement of large samples for which a stand cannot be used.
- The supplied weights are used for calibrating the spring tension of Durometers.




Hardmatic HH-300

Test Block Set

Holding Bar

The holding bar is used to mount a Durometer on a drill press.



64AAA964



64AAA963



905693

811-332

Item No.	Description
64AAA964	Calibration Set (Shore A Scale) Test Block 30* DURO (Blue) Test Block 60* DURO (Yellow) Test Block 90* DURO (Gray) Mahogany Box
64AAA590	Calibration Set (Shore D Scale) Test Block 20* DURO (Blue) Test Block 40* DURO (Gray) Test Block 80* DURO (Black)
64AAA962	"A" Scale Durometer Stand
64AAA794	"A" Scale Durometer Stand with Air Damper
64AAA796	Combination "D" & "A" Scale Durometer Stand
64AAA963	O-Ring Fixture Set 1/16", 3/32", 1/8", 3/16" and 1/4" O-Ring cross sections
19BAA406	Digimatic Miniprocessor with printer
905693	Connecting Cable 40" (1m) for Durometer and Digimatic Miniprocessor

* Values shown are nominal only. Test Block Size 2" x 2" x 1/4"