

# SI 1000 series

Panel mount display controllers



actual size

**With a Display/Controller to match the output from Solartron Metrology's extensive range of Displacement and Gauging transducers, there is now a simple to use and cost effective single channel solution to a wide range of laboratory and industrial linear position monitoring and control applications.**

The versatile **SI 1100** provides up to  $0.1\mu$  resolution when used with Solartron's LVDT Displacement and Gauging transducers. A choice of VDC, 4-20 mA, outputs and relays make it easy to communicate with PLC's. RS232 and RS485 serial ports are also standard.

Where long cable runs are required, the **SI 1300** is an obvious choice. Two wire loop powered 4-20 mA connection to Solartron's S and SR Series of rugged Displacement Transducers completes a simple to install system with an impressive performance. DC/DC operation is also standard for use with the DC versions of the S and SR series.

The **SI 1500** is a cost effective yet versatile panel mount display for use with Solartron's high performance Orbit<sup>®</sup> based Digital Probes, Linear Encoders and Modules.

- Red 7 digit display
- LVDT input (SI1100)
- DC or 4-20 mA inputs (SI 1300)
- Solartron Orbit input (SI 1500)
- RS232 or RS485 Serial outputs
- VDC or 4-20 mA outputs
- Low, OK, High lamps and relays
- Peak Hold

# SI 1000 series

## Specification



Dimensions	SI 1100 LVDT	SI 1300 4-20 mA/Voltage	SI 1500 Digital Probe
Case size (incl. bezel)	H = 48mm x W = 96 x D = 137mm		
Panel cut out	H = 44.5mm x W 93mm		
Depth behind panel (inc. terminals)	135mm		
Display			
Display Type	7 digit red led		
Display Update Rate	Up to 10 readings/second		
Indicators	Low, OK and High warning lamps		
Range	-99.9999 to +99.9999		
Resolution	1mm to 0.1um (user selectable)		
Inputs			
Transducer Types	LVDT AX analogue probes S Series & Miniature LVDT displacement sensors	4-20 mA or 0-10 VDC	Digital probes Orbit modules
Bandwidth/response time /sensor reading rate	Up to 100 readings/second		
Discrete Inputs	Zero, Peak(+Peak/-Peak/Difference), Hold		
Outputs			
Analogue	4-20 mA, -5V to +5V, -10V to +10V, 0V to +5V, 0V to +10V (selectable)		
Discrete	Alarm Relay - Open Collector Low, OK and High Relay Response Time = 0.1-9.9 seconds (selectable)		
Communications			
Serial Port	RS232 or RS485 Configurable		
Power			
Voltage	+24 VDC		
Current	850 mA Max		
Environmental			
Operating Temperature	10°C to 40°C		
Storage Temperature	-10°C to 70°C		
Electrical Immunity	EN6100-6-2:2007		
Electrical Emissions	EN61000-6-3:2007		
Front Panel Sealing	IP65		



**solartron**  
metrology

### Offices worldwide

Agent and distributor details available at  
[www.solartronmetrology.com](http://www.solartronmetrology.com)

**United Kingdom - Head Office**  
Solartron Metrology  
Steyning Way  
Bognor Regis  
West Sussex  
PO22 9ST  
Tel: +44 (0) 1243 833333  
Fax: +44 (0) 1243 833322  
Sales.solartronmetrology@ametek.com

**Germany**  
Ametek GmbH  
Solartron Metrology Division  
Rudolf-Diesel-Strasse 16  
40670 Meerbusch  
Tel: +49 (0) 2159 9136 500  
Fax: +49 (0) 2159 9136 505  
vertrieb.solartron@ametek.de

**France**  
Solartron Metrology  
Rond-point de l'Espine des Champs  
Buroplus - Bat. D  
Elancourt 78990  
Tel: +33 (0)1 30 68 89 50  
Fax: +33 (0)1 30 68 89 59  
france.solartronmetrology@ametek.com

**China**  
*Shanghai*  
Solartron Metrology  
Rm 912, Metro Tower  
No 30 Tian Yao Qiao Road  
Shanghai 200030  
Zhong Renmin Gongheguo  
Tel: +86 21 6426 8111  
Fax: +86 21 6426 7054  
china.solartronmetrology@ametek.com

*Beijing*  
Solartron Metrology  
Rm 912, Metro Tower  
No 30 Tian Yao Qiao Road  
Shanghai 200030  
Tel: +86 21 6426 8111  
Fax: +86 21 6426 7054  
china.solartronmetrology@ametek.com

*Chengdu*  
AMETEK ChengDu Rep Office  
Room 2408, Zongfu Building  
35 Zongfu Road  
Chengdu, Sichun, 610016  
Tel: +86 28 8675 8111  
Fax: +86 28 8675 8141  
china.solartronmetrology@ametek.com

**Japan**  
Solartron Metrology  
4-5-37 Kamiosaki  
Shinagawa-ku  
Tokyo 141-0021  
Tel: +81 (0)3 3494 5131  
Fax: +81 (0)3 3494 5134  
japan.solartronmetrology@ametek.com

**USA**  
915 N. New Hope Road  
Suite C,  
Gastonia, NC 28054  
Tel: +1 800 873 5838  
Fax: +1 704 868 8466  
usasales.solartronmetrology@ametek.com

Solartron pursues a policy of continuous development. Specifications in this document may therefore be changed without notice.

**AMETEK**  
ULTRA PRECISION TECHNOLOGIES